



Dimensions and weights

pump type	DIMENSIONS [mm]								Net Weight [kg]	
	* B1		* B2		** B1+B2		D1	D2	*	**
	B1	B2	B1+B2	B1	B1+B2	D1	D2	*	**	
GPR2-20	220	190	410	245	435	140	110	20	25	
GPR2-30	240	190	430	265	455	140	110	20	25	
GPR2-40	260	190	450	285	475	140	110	20	25	
GPR2-50	275	190	465	300	490	140	110	20	25	
GPR2-60	300	230	530	325	555	140	110	20	25	
GPR2-70	315	230	545	340	570	140	110	25	30	
GPR2-90	350	230	580	375	605	140	110	30	35	
GPR2-110	385	230	615	410	640	140	110	30	35	
GPR2-130	440	280	720	465	745	180	110	30	35	
GPR2-150	475	280	755	500	780	180	110	30	35	
GPR2-180		280		555	835	180	110		50	
GPR2-220		280		625	905	180	110		55	
GPR2-260		335		705	1040	180	110		60	

* GPR2 With Oval flanges
 ** GPR2 With DIN flanges
 Pipework connection
 DIN 2566 with threaded socket
 DIN/2634/2635 with socket for welding
 * Oval flange base for pump models GPR2-20 to GPR2-150
 ** DIN flange base for pump models GPR2-20 to GPR2-260

